



AIRMAN[®]
AIR COMPRESSORS

PDS375DP-6E1
375-330 cfm

AIRMAN air compressors are manufactured to the highest quality, consistently delivering the industry's best return on investment.

ANA is committed to supplying the finest products with unmatched performance and support, maintaining their value over time.

- 375-330 cfm Free Air Delivery
- Best-in-Class Fuel Efficiency
- Kubota Diesel Engine
- EPA Tier 4F & CARB Compliant



Alliance North America

Phone: 562-450-3570

E-mail: sales@anacorp.com

www.anacorp.com

California: 11100 Hope Street • Cypress, CA 90630

Texas: 10440 Brockwood Road • Dallas, Texas 75238

South Carolina: 4220 S. Church St. • Roebuck, SC 29376

© COPYRIGHT 2020, ANA • 071720

AIRMAN is a trademark of HOKUETSU INDUSTRIES CO., LTD.

Features and specifications may change without notice. Please consult ANA for all current information.

SPECIFICATIONS



AIRMAN[®]

AIR COMPRESSORS

PDS375DP-6E1

375-330 cfm

COMPRESSOR SPECIFICATIONS

Type	Dual Pressure, Oil Cooled, Screw-Type
Free Air Delivery	375 cfm @100 psi; 330 cfm @ 150 psi
Working Pressure	100 psig
Max. Working Pressure	150 psig
Air Outlets	2" x 1; ¾" x 2
Engine Coupling Type	Rubber coupling
Lubrication System Type	Forced lubrication by compressed air
Lubrication System Capacity	10.6 gal.
Oil Cooler Type	Separate side-by-side oil cooler and radiator

ENGINE SPECIFICATIONS

Model / EPA Emission Level	Kubota V3800 / Tier 4 Final
Engine Type	Water Cooled 4-Cycle, Direct-Injection, Turbocharged Air-To-Air Intercooled, EGR, DOC+DPF, SCR Tier 4F & CARB Compliant
Cylinders	4
Displacement	230 cu.in. (3.769 L)
Fuel Type	Diesel
Output	110.4 HP (82.3 kW)
Low Idle	1300 rpm
High Idle	2400-2700 rpm
Fuel Tank Capacity	47.0 gal.
Oil Capacity	3.4 gal.
DEF Tank Capacity	5.3 gal.
Cooling System Capacity	4.1 gal.
Battery	12V 130F51

FUEL CONSUMPTION

FULL load	5 gph @100 psi; 5.1 gph @ 150 psi
75% load	3.75 gph @100 psi; 3.825 gph @150 psi
50% load	2.5 gph @100 psi; 2.55 gph @150 psi
Run time @ full load	9.25 hr.

WEIGHTS AND DIMENSIONS

Dry Weight	3,737 lb.
Weight w/ Towing Frame	3,975 lb.
Operating Weight	4,233 lb.
LxWxH w/o Towing frame	106" x 55" x 60"
LxWxH w/ Towing frame	174" x 57" x 69"

OPERATING PARAMETERS

Min. Ambient Temperature	5° F
Max. Incline	15°
Sound Level	76 dBA



Alliance North America

Phone: 562-450-3570

E-mail: sales@anacorp.com

www.anacorp.com

California: 11100 Hope Street • Cypress, CA 90630

Texas: 10440 Brockwood Road • Dallas, Texas 75238

South Carolina: 4220 S. Church St. • Roebuck, SC 29376