



AIRMAN[®]
AIR COMPRESSORS

PDS400S-6E1
400 cfm

AIRMAN air compressors are manufactured to the highest quality, consistently delivering the industry's best return on investment.

ANA is committed to supplying the finest products with unmatched performance and support, maintaining their value over time.

- 400 cfm Free Air Delivery
- Best-in-Class Fuel Efficiency
- Kubota Diesel Engine
- EPA Tier 4F & CARB Compliant
- Available with built-in aftercooler



Alliance North America

Phone: 562-450-3570

E-mail: sales@anacorp.com

www.anacorp.com

California: 11100 Hope Street • Cypress, CA 90630

Texas: 10440 Brockwood Road • Dallas, Texas 75238

South Carolina: 4220 S. Church St. • Roebuck, SC 29376

© COPYRIGHT 2020, ANA • 120820

AIRMAN is a trademark of HOKUETSU INDUSTRIES CO., LTD.

Features and specifications may change without notice. Please consult ANA for all current information.

SPECIFICATIONS



AIRMAN[®]

AIR COMPRESSORS

PDS400S-6E1

400 cfm

COMPRESSOR SPECIFICATIONS

Type	Single-Stage, Oil Cooled, Screw Type
Free Air Delivery	400 cfm
Working Pressure	100 psig
Max. Working Pressure	125 psig
Air Receiver Tank Capacity	25.88 gal
Air Outlets	1 x 2"; 2 x ¾"
Engine Coupling Type	Rubber coupling
Lubrication System Type	Forced lubrication by compressed air
Lubrication System Capacity	10.6 gal.
Oil Cooler Type	Separate side-by-side oil cooler and radiator

ENGINE SPECIFICATIONS

Model	Kubota V3800-T4F
Type	Water-Cooled 4-Cycle, Direct-Injection, Turbocharged Air-to-Air Intercooled, EGR, DOC+DPF, SCR Tier 4F & CARB Compliant
Cylinders	4
Displacement	230 cu.in. (3.769 L)
Horsepower	108 hp (80.5 kw)
Low Idle	1350 rpm
High Idle	2600 / 2400-2700 rpm
Fuel Consumption	4.62 gal./hr.
Fuel Capacity	47.0 gal.
Def Tank Capacity	5.3 gal.
Cooling System Capacity	4.1 gal.
Oil Capacity	3.4 gal.
Electrical System	130F51x1 (12V) Maintenance-Free Battery

WEIGHTS AND DIMENSIONS

Dry Weight	3,550 lb.
Weight w/ Towing Frame	3,975 lb.
Operating Weight	4,012 lb.
LxWxH w/o Towing frame	106" x 55" x 60"
LxWxH w/ Towing frame	174" x 69" x 69"

OPERATING PARAMETERS

Min. Ambient Temperature	5° F
Max. Incline	15°
Sound Level	76 dBA

NOTE

This unit is also available with built-in aftercooler — specify model **PDS400SC-6E1**



Alliance North America

Phone: 562-450-3570

E-mail: sales@anacorp.com

www.anacorp.com

California: 11100 Hope Street • Cypress, CA 90630

Texas: 10440 Brockwood Road • Dallas, Texas 75238

South Carolina: 4220 S. Church St. • Roebuck, SC 29376