



VPump 20^{HP}
INVERTER

**25
kVA**

**PRIME
POWER**



Built in 480V VFD/Inverter for better motor starting and speed control

PERFORMANCE //

- 1 - DSE® Digital Control Panel
- 2 - Curbside Electrical Panel
- 3 - Voltage Selector with 480V Inverter Position
- 4 - Emergency Stop Button
- 5 - Delta Demand Excitation™
- 6 - QuietTech™ Sound Attenuation
- 7 - Variable Frequency Drive

MAINTENANCE //

- 8 - Lift-off Door Hinges
- 9 - Ext. Fuel Tank Connections
- 10 - 110% Fluid Containment
- 11 - Service Extensions
- 12 - Fuel & Containment Drains
- 13 - Removable Trailer Fenders

CONSTRUCTION //


- 14 - Power-coated Steel Enclosure
- 15 - Stainless Steel Hardware
- 16 - Lockable Access Doors
- 17 - Automotive Door Seals
- 18 - 51.5 Gallon Fuel Tank
- 19 - Heavy-Duty Steel Trailer with Lockable Storage




ISUZU® 4LE2T
Tier 4 / CARB
Diesel Engine



1 | DSEgenset® Digital Control Panel with VFD/Inverter Controls



2 | Output Panel
120V - 20A x 2 | 240V - 50A x 2 with Terminal Block for VFD Remote Control



3 | Lockable Voltage Selector Switch
3φ 480V Interter 480V/277V and 120/208-139/240V 1φ 120/240V



7 | 480V Variable Frequency Drive with Cooling Fans

BEST-IN-CLASS dBA RATING // 24-HOUR RUNTIME \\\ EXCELLENT MOTOR STARTING
THE INDUSTRY'S HIGHEST-QUALITY MOBILE GENERATORS

GENERATOR MODEL SDG25SV-8E1

AIRMAN® MOBILE GENERATORS



GENERATOR SPECIFICATIONS	SDG25SV-8E1
ALTERNATOR TYPE	AIRMAN WYE Winding
STANDBY OUTPUT	
THREE-PHASE AT 240V 3CD-4 WIRE	27.5 kVA / 22 kW
SINGLE-PHASE AT 240V 1CD-3 WIRE	15.8 kVA / 15.8 kW
PRIME OUTPUT	
THREE-PHASE AT 240V 3CD-4 WIRE	25 kVA / 20 kW
SINGLE-PHASE AT 240V 1CD-3 WIRE	14.4 kVA / 14.4 kW
FREQUENCY	60 Hz
VOLTAGE (THREE-PHASE), SWITCHABLE	480/277 240/139
VOLTAGE (SINGLE-PHASE), SWITCHABLE	240/120
ARMATURE CONNECTION	Star with Neutral/Zig Zag
EXCITATION	Brushless with AVR
NUMBER OF POLES	4
INSULATION	Class F
VOLTAGE REGULATION	±0.5%
FREQUENCY REGULATION, STEADY STATE	±0.25% of Overall Mean Value
AMPERAGE	
SINGLE-PHASE (120V) - ZIG ZAG	60A x 2
SINGLE-PHASE (240V) - ZIG ZAG	60A
THREE-PHASE (208V)	65A
THREE-PHASE (240V)	60A
THREE-PHASE (480V)	30A
VFD/INVERTER MAKE/MODEL	Mitsubishi® FR-F800
OUTPUT VOLTAGE	400-480V
ADJUSTABLE FREQUENCY RANGE	30-60Hz
FREQUENCY METER	Yes
REVERSE POWER SWITCH	Yes
ENGINE MAKE & MODEL	ISUZU® 4LE2T
ENGINE CONTROL PANEL	DSE® 7310 MKII
EPA TIER 4 CARB/ EMISSION CERTIFIED	Tier 4 Final, Model Year 2023 EPA & CARB Certification
TYPE OF AFTERTREATMENT	Diesel Oxidation Catalyst (DOC)

ENGINE MAKE & MODEL (Continued)	ISUZU® 4LE2T
ENGINE TYPE	Direct Injection 4-Cycle Liquid Cooled Diesel, EGR
ASPIRATION	Turbocharged
SAE GROSS HP / BHP@1800 RPM	40.2 BHP / 30 kW
HORSEPOWER RATING (@1800 RPM)	33.3 HP / 24.8 kW
NUMBER OF CYLINDERS	4
DISPLACEMENT	133 cu in
ENGINE SPEED	1800 RPM
GOVERNOR TYPE	Electronic
FUEL TYPE	Ultra-low sulfur diesel (ULSD)
FUEL TANK CAPACITY	52 gal
FUEL CONSUMPTION	
FULL LOAD	1.6 gal/hr
75% LOAD	1.3 gal/hr
50% LOAD	1.0 gal/hr
RUNTIME @ FULL LOAD	32 hrs
FUEL PUMP	Self-priming Electric Fuel Pump
FUEL FILTER TYPE / QUANTITY	Combination Fuel/Filter Sedimentator x 1
LUBRICATING OIL CAPACITY	4.1 gal
BATTERY	
SYSTEM VOLTAGE	12V
BATTERY CHARGER ALTERNATOR QUANTITY	35 A 1
COLD CRANKING AMPS	490 CCA
AMP HOURS	70 Ah
COOLING SYSTEM	
COOLING SYSTEM TYPE	Liquid/Air Fin and Tube Radiator, 50/50 Mix
COOLANT CAPACITY	2.75 gal
WATER PUMP TYPE	Impeller
FAN TYPE	Belt-driven Pusher
NOISE LEVEL @ 23 FEET(NO/FULL LOAD)	61 dBA / 63 dBA

ENCLOSURE	
PAINT TYPE	Positively Charged Ion (E-coat) Electrodeposition Coating, Baking Finish Coating for Weatherproof, and Anti-corrosion and Salt Pollution
ENCLOSURE METAL / CONSTRUCTION	Steel
GAUGE STEEL	16 Gauge
DOOR HINGES	Stainless Steel
SERVICE ACCESS POINTS HARDWARE	Stainless Steel
SPILL CONTAINMENT	110%
WEIGHTS & DIMENSIONS	
LENGTH x WIDTH x HEIGHT	67" x 35" x 55"
DRY WEIGHT	1,830 lbs
OPERATING WEIGHT	2,227 lbs
TRAILER WEIGHT	690 lbs
OPERATING WEIGHT w/ TRAILER	2,917 lbs
TRAILER WEIGHTS & DIMENSIONS	
LENGTH	119"
WIDTH	67"
HEIGHT w/ GENERATOR INSTALLED	71"
WEIGHT	690 lbs
WHEEL SIZE-TIRE RATING	ST205/75R15 Load Limit C-1820 lbs @ 50 psi
NUMBER OF AXLES / RATING	1 Axle / 3,700 lbs each
BRAKING TYPE	None
LIGHTING TYPE	LED
CERTIFICATIONS USA/DOT COMPLAINT	FMVSS
ADJUSTABLE HITCH HEIGHT	Yes
COMPLIANCE & CERTIFICATIONS	
FLUID CONTAINMENT	110%
USA DOT COMPLIANT	Yes
CSA LISTED	Yes
TRANSPORT CANADA COMPLIANT	Yes
DIESEL ENGINE EPA TIER LEVEL	Tier 4 Final

Patents Pending - All specifications are subject to change without prior notice. Visit anacorp.com for the most current information.

SMARTLOAD™ LOAD BANK SYSTEM



Single Row Cam-Loks™



Fuel Filter Heater

ACCESSORIES & OPTIONS

- ◀ SmartLoad™ System
- ◀ Single Row Cam Loks™
- ◀ Fuel Filter Heater
- Battery Blanket
- Lockable Battery Disconnect
- Engine Coolant Heater
- Engine Block Heater
- Battery Charger
- 600V
- 🇨🇦 CSA Certification
- 5-Yr./10,000-Hr. Ext. Warranty



SOLD AND SERVICED BY

ANA
Nevada
1740 Raiders Way
Henderson, NV 89052

ANA
S. California
11100 Hope Street
Cypress, CA 90630

ANA
N. California
1315 Vinci Avenue
Sacramento, CA 95838

ANA
South Carolina
1335 Hayne Street
Spartanburg, SC 29301



ANA, Inc.
Executive Office
1770 Raiders Way, Henderson, NV 89052

ANACORP.COM
(562) 450-3570 // sales@anacorp.com



ANA®

We make your world easier.