



### PERFORMANCE //

- 1 10" Touchscreen Control Panel
- 2 CAM-Lok™ Input Connection
- 3 Emergency Stop Button
- 4 Telematics Monitoring System
- 5 Simul. Voltage Output Panel

- 6 Powder-coated Steel Enclosure
- 7 Stainless Steel Hardware
- 8 Lockable Access Doors

## CONSTRUCTION //

- 9 Heavy-Duty Steel Trailer

# MAINTENANCE //

- 10 Service Extensions
- 11 Removable Trailer Fenders





2 | Convenient CAM-Lok Input Connection 3Ф 480V Cam-Loks™



4 | Telematics Monitoring System Remote access and monitoring of fuel, runtime, GPS, load and more



5 | Simultaneous Voltage Output Panel 120V - 20A x 4 | 240V - 1Ф x3 3Ф 240V & 3Ф 208/480v Cam-Loks™



# HYBRID ENERGY SYSTEM MODEL BOSS70-25 - Head Unit Only





SPECIFICATIONS	BOSS70-25
HYBRID ENERGY SYSTEM	ANA Energy Boss™
MAXIMUM INTERMITTENT POWER OUTPUT	(Battery SOC Greater than 5%)
THREE-PHASE	70 kVA / 56 kW
SINGLE-PHASE	47 kVA / 37 kW
FREQUENCY	60 Hz
VOLTAGE (THREE-PHASE), SIMULTANEOUS	120 / 208 / 277 / 480
VOLTAGE (SINGLE-PHASE), SIMULTANEOUS	120 / 240
VOLTAGE REGULATION	Adjustable
MAXIMUM CONTINUOUS POWER OUTPUT	(Battery SOC at 0%)
THREE-PHASE OUTPUT	45 kVA / 36 kW
SINGLE-PHASE OUTPUT	30 kVA / 24 kW
SIMULTANEOUS VOLTAGE (THREE-PHASE)	120 / 208 / 277 / 480
SIMULATANEOUS VOLTAGE (SINGLE-PHASE)	120 / 240
CONTROLS	
CONTROL PANEL	10" Full Color Touch Screen
TELEMATICS	Energy Boss™
ESG REPORTING	Yes
TECHNOLOGY	
BATTERY CHEMISTRY	Lithium Titanate Oxide (LTO)
BATTERY CAPACITY	25 kWh
TOTAL BATTERY LIFE OR ENERGY THROUGHOUT	2,000 MWh
CHARGE TIME (NO LOAD)	≈ 45 min
INVERTER OUTPUT MAX	56 kW
BATTERY LIFE*	
BATTERY TYPE	Lithium Titanate Oxide (LTO)
BATTERY SIZE	25 kWh
EST. CYCLE LIFE @ 77°F ENCLOSURE TEMPERATURES	90K Cycles at 90% DOD
EST. CYCLE LIFE @ 100°F ENCLOSURE TEMPERATURES	80K Cycles at 90% DOD
BATTERY LIFE (100° F @ 11 kW AVERAGE LOAD)	20 Years
OPERATING TEMPERATURES	
INVERTER COLD START TEMPERATURE (MINIMUM)	14°F
RUNNING OPERATING TEMPERATURE	-22°F to 130°F
ARCTIC PACKAGE OPERATING TEMP. (OPTIONAL)	-50°F to 130°F
BATTERY CHARGING TEMPERATURE	-22°F to 130°F
FEATURES & OPTIONS	
TRAILER MOUNT	Available
SKID MOUNT	Available
ROOF MOUNTED SOLAR FOR EBOSS BATTERY, 3 PANELS (1.6 kW)	Available
PARALLEL CAPABILITY	Available
COLD WEATHER/ARCTIC PACKAGES	Available

LxWxH	55" x 44" x 62"
EBOSS WEIGHT	2,513 lbs
<b>ENERGY BOSS COLD WEATHER OPTIONS</b>	5
Enclosure Heater	Available at Launch
Magnetic Ventillation Covers	Available at Launch
WARRANTY	
ENERGY BOSS™	2 Years
MANUFACTURER BATTERY WARRANTY	7 Years
SERVICE & SUPPORT	24/7, 365 Days
TRAINING	Henderson, NV or On Location

# **Skid Mount Option Available**

For Energy Boss™ head unit only models.



Ask your sales rep about all possible configurations.

SOLD AND SERVICED BY

All specifications are subject to change without prior notice. Contact ANA Inc. for the most current information.

#### ANA ENERGY BOSS™ HYBRID ENERGY SYSTEMS BENEFITS

- · Increased Fuel Efficiency
- Reduced Green House Gas Emissions
- Cost Effective High ROI
- Minimize Noise / Maximize Quiet Time
- Eliminate Maintenance Needs and Operational Hours by up to 75%
- · Remote Access and Monitoring

1740 Raiders Way Henderson, NV 89052

11100 Hope Street Cypress, CA 90630

1315 Vinci Avenue Sacramento, CA 95838 1335 Hayne Street Spartanburg, SC 29301

ANA, Inc. Executive Office

**ANACORP.COM** 

(562) 450-3570 // sales@anacorp.com



1770 Raiders Way, Henderson, NV 89052

<sup>\*</sup>Battery expected to retain 95% of its life after 7 years under 24/7 operation at 3kW average load.