

**150  
kVA** PRIME  
POWER



Shown equipped with optional  
**SMARTLOAD™**  
LOAD BANK SYSTEM

#### PERFORMANCE //

- 1 - DSE® Digital Control Panel
- 2 - Curbside Electrical Panel
- 3 - Large Electrical Lugs
- 4 - Emergency Stop Button
- 5 - Delta Demand Excitation™
- 6 - Quietech™ Sound Attenuation
- 7 - Lockable Voltage Selector

#### MAINTENANCE //

- 8 - Lift-off Door Hinges
- 9 - 110% Fluid Containment
- 10 - Ext. Fuel Tank Connections
- 11 - Built-in Service Ladder
- 12 - Service Extensions
- 13 - Front DEF Access Door

#### CONSTRUCTION //

- 14 - Powder-coated Steel Enclosure
- 15 - Stainless Steel Hardware
- 16 - Lockable Access Doors
- 17 - Automotive Door Seals
- 18 - 204 Gallon Fuel Tank
- 19 - Heavy-Duty Steel Trailer



John Deere® 6068  
Tier 4 / CARB  
Diesel Engine



**1** | DSEgenset® Digital Control Panel  
Model 7310 MKII



**2** | Single-Phase Receptacles  
120V - 20A x 2 - | 240V - 50A x 3  
Optional Dual Row Cam-Loks™ Shown



**7** | Lockable Voltage Selector Switch  
3Φ 277/480V & 139/240V-120/208V  
1Φ 120/240V



**10** | External Fuel Tank Connections  
with 3-Way Selection Valve

**BEST-IN-CLASS dBA RATING // 24-HOUR RUNTIME // EXCELLENT MOTOR STARTING**  
**THE INDUSTRY'S HIGHEST-QUALITY MOBILE GENERATORS**

# GENERATOR MODEL SDG150S-8E1



GENERATOR SPECIFICATIONS	SDG150S-8E1
ALTERNATOR TYPE	TAIYO WYE Winding
<b>STANDBY OUTPUT</b>	
THREE-PHASE AT 240V 3CD-4 WIRE	165 kVA / 132 kW
SINGLE-PHASE AT 240V 1CD-3 WIRE	95.7 kVA / 95.7 kW
<b>PRIME OUTPUT</b>	
THREE-PHASE AT 240V 3CD-4 WIRE	150 kVA / 120 kW
SINGLE-PHASE AT 240V 1CD-3 WIRE	87 kVA / 87 kW
FREQUENCY	60 Hz
VOLTAGE (THREE-PHASE), SWITCHABLE	208/220/240/416/440/480
VOLTAGE (SINGLE-PHASE), SWITCHABLE	120/127/139/240/254/277
ARMATURE CONNECTION	Star with Neutral / Zig Zag
EXCITATION	Brushless with AVR
NUMBER OF POLES	4
POWER FACTOR (THREE-PHASE)	0.8
POWER FACTOR (SINGLE-PHASE)	1.0
INSULATION	Class F
VOLTAGE REGULATION	±0.5%
FREQUENCY REGULATION, STEADY STATE	±0.25% of Overall Mean Value
<b>AMPERAGE</b>	
SINGLE-PHASE (120V) - ZIG ZAG	363A x 2
SINGLE-PHASE (240V) - ZIG ZAG	363A
THREE-PHASE (208V)	394A
THREE-PHASE (240V)	361A
THREE-PHASE (480V)	180A
<b>ENGINE MAKE &amp; MODEL</b>	<b>JOHN DEERE® 6068</b>
ENGINE CONTROL PANEL	DSE® 7310 MKII
EPA TIER 4 / CARB EMISSION CERTIFIED	Tier 4 Final, Model Year 2023 EPA & CARB Certification
TYPE OF AFTERTREATMENT	DEF, DOC, SCR, ASC
ENGINE TYPE	Electronic Direct Injection 4-Cycle Liquid Cooled Diesel
ASPIRATION	Turbocharged + Turbo After Cooler

ENGINE MAKE & MODEL (Continued)	JOHN DEERE® 6068
SAE GROSS HP / BHP@1800 RPM	257 BHP / 192 kW
HORSEPOWER RATING (@1800 RPM)	235 HP / 175 kW
NUMBER OF CYLINDERS	6
DISPLACEMENT	415 cu in
ENGINE SPEED	1800 RPM
GOVERNOR TYPE	Electronic
FUEL TYPE	Ultra-low sulfur diesel
DEF CAPACITY	11.7 gal
DEF CONSUMPTION (MAXIMUM)	4.1 gal Per Tank of Diesel
DEF RUNTIME @ FULL LOAD	67 hrs
FUEL TANK CAPACITY	204 gal
<b>FUEL CONSUMPTION</b>	
FULL LOAD	8.5 gal/hr
75% LOAD	6.9 gal/hr
50% LOAD	5.1 gal/hr
RUNTIME @ FULL LOAD	24 hrs
FUEL PUMP (w/SERVICEABLE STRAINER)	Self-priming Electric Fuel Pump
FUEL FILTER TYPE / QUANTITY	Pre-filter/Sedimentor x 1 Fuel Filter x 1
LUBRICATING OIL CAPACITY	8.7 gal
<b>BATTERY</b>	
SYSTEM VOLTAGE	12V
BATTERY CHARGER ALTERNATOR	90 A
QUANTITY	1
COLD CRANKING AMPS	925 CCA
AMP HOURS	150 Ah
<b>COOLING SYSTEM</b>	
COOLING SYSTEM TYPE	Liquid/Air Fin and Tube Radiator 50/50 Mix
COOLANT CAPACITY	7.1 gal
WATER PUMP TYPE	Impeller
FAN TYPE	Blower Fan, Viscous Clutch
NOISE LEVEL @ 23 FEET (NO/FULL LOAD)	61 dBA / 66 dBA

ENCLOSURE	
PAINT TYPE	Positively Charged Ion (E-coat) Electrodeposition Coating, Baking Finish Coating for Weatherproof, and Anti-corrosion and Salt Pollution
ENCLOSURE METAL / CONSTRUCTION	Steel
GAUGE STEEL	16 Gauge
DOOR HINGES	Stainless Steel
SERVICE ACCESS POINTS HARDWARE	Stainless Steel
SPILL CONTAINMENT	110%
<b>WEIGHTS &amp; DIMENSIONS</b>	
LENGTH x WIDTH x HEIGHT	129.9" x 51.2" x 84.6"
DRY WEIGHT	6,878 lbs
OPERATING WEIGHT	8,488 lbs
TRAILER WEIGHT	1,350 lbs
OPERATING WEIGHT w/TRAILER (GVWR)	9,838 lbs
<b>TRAILER WEIGHTS &amp; DIMENSIONS</b>	
LENGTH	211"
WIDTH	83.75"
HEIGHT W/GENERATOR INSTALLED	100.6"
WEIGHT	1,350 lbs
WHEEL SIZE-TIRE RATING	S125/75R15 Load Limit E, 3520 lbs @ 80 psi
NUMBER OF AXLES / RATING	2 Axles / 6,000 lbs each
BRAKING TYPE	Surge or Electric
LIGHTING TYPE	LED
CERTIFICATIONS USA/DOT COMPLIANT	FMVSS
ADJUSTABLE HITCH HEIGHT	Yes
<b>COMPLIANCE &amp; CERTIFICATIONS</b>	
FLUID CONTAINMENT	110%
USA DOT COMPLIANT	Yes
CSA LISTED	Yes
TRANSPORT CANADA COMPLIANT	Yes
DIESEL ENGINE EPA TIER LEVEL	Tier 4 Final

All specifications are subject to change without prior notice. Visit [anacorp.com](http://anacorp.com) for the most current information.

## SMARTLOAD™

### LOAD BANK SYSTEM

- U.S. PATENT PENDING -



SmartLoad™ System



Parallelling Control Panel

### ACCESSORIES & OPTIONS

- ◀ SmartLoad™ System
- ◀ Parallelling Feature
- Dual Row Cam-Loks™ (See Front)
- 4-Position Selector Switch
- Lockable Battery Disconnect
- Fuel Filter Heater
- Engine Coolant Heater
- Engine Block Heater
- Battery Charger
- Battery Blanket
- 600V
- CSA Certification
- 5-Yr./10,000-Hr. Ext. Warranty



SOLD AND SERVICED BY

**ANA Nevada**  
1740 Raiders Way  
Henderson, NV 89052

**ANA S. California**  
11100 Hope Street  
Cypress, CA 90630

**ANA N. California**  
1315 Vinci Avenue  
Sacramento, CA 95838

**ANA South Carolina**  
1335 Hayne Street  
Spartanburg, SC 29301

**ANA Texas**  
10440 Brockwood Road  
Dallas, TX 75338



### ANA, Inc.

Executive Office

1770 Raiders Way, Henderson, NV 89052

**ANACORP.COM**

(562) 450-3570 // [sales@anacorp.com](mailto:sales@anacorp.com)



# ANA

We make your world easier.