



EBOSS®
70kVA
- POWER MODULE -

45/70 PRIME/PEAK
kVA POWER

20X

UP TO 20X THE
CYCLE LIFE OF
NMC/LFP BATTERIES



SAFE BATTERY
TECHNOLOGY
NO THERMAL RUNAWAY



WIDEST
TEMPERATURE
OPERATING RANGE



SIMULTANEOUS
OUTPUT
VOLTAGES



REMOTE ACCESS
MONITORING &
TRACKING



INDUSTRIAL
GRADE
INVERTERS



**25 kWh ULTRA
HIGH CYCLE**
LITHIUM TITANATE OXIDE (LTO)
BATTERY CHEMISTRY

PERFORMANCE //

- 1 - 10" Touchscreen Control Panel
- 2 - CAM-Lok™ Input Connection
- 3 - Emergency Stop Button
- 4 - Telematics Monitoring System
- 5 - Simul. Voltage Output Panel

CONSTRUCTION //

- 6 - Powder-coated Steel Enclosure
- 7 - Stainless Steel Hardware
- 8 - Lockable Access Doors
- 9 - Heavy-Duty Steel Trailer

MAINTENANCE //

- 10 - Service Extensions
- 11 - Removable Trailer Fenders



2 | Convenient CAM-Lok Input Connection
3Φ 480V Cam-Loks™



4 | Telematics Monitoring System
Remote access and monitoring of fuel,
runtime, GPS, load and more



5 | Simultaneous Voltage Output Panel
120V - 20A x 4 | 240V - 1Φ x 3
3Φ 240V & 3Φ 208/480v Cam-Loks™

IMPROVE FUEL ECONOMY // LOWER CARBON EMISSIONS // REDUCE NOISE LEVELS
THE INDUSTRY'S HIGHEST-QUALITY HYBRID POWER SYSTEMS

POWER MODULE MODEL EBOSS[®] 70kVA



SPECIFICATIONS	EBOSS 70kVA Power Module
HYBRID ENERGY SYSTEM	ANA EBOSS
MAXIMUM INTERMITTENT POWER OUTPUT	(Battery SOC Greater than 5%)
THREE-PHASE	70 kVA / 56 kW
SINGLE-PHASE	47 kVA / 37 kW
FREQUENCY	60 Hz
SIMULTANEOUS VOLTAGE	120/240 (1Φ) - 208/480 (3Φ)
VOLTAGE REGULATION	Adjustable
MAX. INTERMITTENT AMP-LOAD @208V	194 A
MAX. INTERMITTENT AMP-LOAD @480V	84 A
MOTOR START RATING - 3 SECOND @208V	291 A
MOTOR START RATING - 3 SECOND @480V	126 A
MAXIMUM CONTINUOUS POWER OUTPUT	(Battery SOC greater than 0%)
THREE-PHASE OUTPUT	42 kVA / 33 kW
SINGLE-PHASE OUTPUT	28 kVA / 22 kW
SIMULTANEOUS VOLTAGE	120/240 (1Φ) - 208/480 (3Φ)
MAX. CONTINUOUS AMP-LOAD @208V	119 A
MAX. CONTINUOUS AMP-LOAD @480V	54 A
CONTROLS	
CONTROL PANEL	10" Full Color Touch Screen
TELEMATICS	Generator & EBOSS
ESG REPORTING	Yes
TECHNOLOGY	
BATTERY CHEMISTRY	Lithium Titanium Oxide (LTO)
BATTERY CAPACITY	25 kWh
TOTAL BATTERY LIFE OR ENERGY THROUGHOUT	2,000 MWh
CHARGE TIME (NO LOAD)	≈ 45 Minutes
INVERTER OUTPUT MAX	56 kW
BATTERY LIFE*	
BATTERY TYPE	Lithium Titanium Oxide (LTO)
EST. CYCLE LIFE @ 77°F ENCLOSURE TEMPERATURES	90K Cycles at 90% DOD
EST. CYCLE LIFE @ 100°F ENCLOSURE TEMPERATURES	80K Cycles at 90% DOD
BATTERY LIFE (100°F @ 3 kW AVERAGE LOAD)	20 Years
OPERATING TEMPERATURES	
INVERTER COLD START TEMPERATURE (MINIMUM)	14°F
RUNNING OPERATING TEMPERATURE	-22°F to 130°F
ARCTIC PACKAGE OPERATING TEMP. (OPTIONAL)	-50°F to 130°F
FEATURES & OPTIONS	
TRAILER MOUNT	Available
SKID MOUNT	Available
ROOF MOUNTED SOLAR FOR EBOSS BATTERY, 3 PANELS (1.6 kW)	Available
PARALLEL CAPABILITY	Available
COLD WEATHER/ARCTIC PACKAGES	Available

*Battery expected to retain 95% of its life after 7 years under 24/7 operation at 10% average load.

All specifications are subject to change without prior notice. Contact ANA Inc. for the most current information.

ANA EBOSS[®] HYBRID ENERGY SYSTEMS BENEFITS

- Increased Fuel Efficiency
- Reduced Green House Gas Emissions
- Cost Effective High ROI
- Minimize Noise / Maximize Quiet Time
- Eliminate Maintenance Needs and Operational Hours by up to 75%
- Remote Access and Monitoring

WEIGHTS & DIMENSIONS	
L x W x H	55" x 44" x 62"
EBOSS WEIGHT	2,700 lbs
ENERGY BOSS COLD WEATHER OPTIONS	
Enclosure Heater	Available
Magnetic Ventillation Covers	Available
WARRANTY	
ENERGY BOSS [™]	2 Years
MANUFACTURER BATTERY WARRANTY	7 Years
SERVICE & SUPPORT	24/7, 365 Days
TRAINING	Henderson, NV or On Location

Skid Mount Option Available

For Energy Boss[™] head unit only models.



Ask your sales rep about all possible configurations.

SOLD AND SERVICED BY

**ANA
Nevada**

1740 Raiders Way
Henderson, NV 89052

**ANA
S. California**

11100 Hope Street
Cypress, CA 90630

**ANA
N. California**

1315 Vinci Avenue
Sacramento, CA 95838

**ANA
South Carolina**

1335 Hayne Street
Spartanburg, SC 29301



ANA, Inc.
Executive Office

1770 Raiders Way, Henderson, NV 89052

ANACORP.COM

(562) 450-3570 // sales@anacorp.com



ANA[®]

We make your world easier.

© 2025 Alliance North America, Inc. All rights reserved.

All other trademarks are property of their respective owners. Form EBOSSREV0225